



白熱灯



150





2,800K





照明率表 P.947-D-



照明率表 P.947-D-



照明率表 P.947-D-



照明率表 P.947-E-

150 埋込穴 ベース 近接限度 0.4m

150 埋込穴 ベース 近接限度 0.4m

150 埋込穴 ベース 近接限度 0.4m

150 埋込穴 ベース 近接限度 0.4m

D72-3865

¥4,300 [ランプ付]



- 枠/銅板 オフホワイト塗装
- 反射板/アルミ シルバー電解(鏡面)
- 0.5kg
- 埋込必要高184mm
- 取付可能天井厚2~50mm

DDL-14521

¥4,700 [ランプ付]



- 枠/銅板 オフホワイト塗装
- 反射板/アルミ シルバー電解(鏡面)
- 0.6kg
- 埋込必要高128mm
- 取付可能天井厚2~25mm

DDL-51028

¥5,500 [ランプ付]



- 枠/銅板 オフホワイト塗装
- パツル/アルミ オフホワイト塗装
- 反射板/アルミ シルバー電解(鏡面)
- 0.4kg
- 埋込必要高183mm
- 取付可能天井厚2~45mm

DDL-14771

¥6,500 [ランプ付]



- 枠/銅板 オフホワイト塗装
- パツル/アルミ オフホワイト塗装
- 反射板/アルミ シルバー電解(鏡面)
- 0.6kg
- 埋込必要高128mm
- 取付可能天井厚2~25mm

